

Dual N-Channel 30 V (D-S) MOSFET

PRODUCT SUMMARY		
V _{DS} (V)	R _{DS(on)} (Ω)	I _D (A)
30	0.014 at V _{GS} = 10 V	12.1
	0.017 at V _{GS} = 4.5 V	11



Features

- Low Gate Charge
- RoHS Compliant

Applications

- Synchronous Buck
 - Notebooks
 - Servers
 - STB

Pin Configuration



Packing Information







Device	Marking	Reel Size	Tape Width	Quantity
EC4202	13D XXX	12"	13mm	3000pcs






Absolute Maximum Ratings (T_J=25 °C Unless Otherwise Noted)


Symbol	Parameter	Value	Unit
P-MOSFET			
V _{DS}	Drain-Source Voltage	30	V
V _{GS}	Gate-Source Voltage	± 20	V
I _D	Continuous Drain Current	12.1	A
I _{DM}	Pulse Drain Current	50	A
P _D	Maximum Power Dissipation	3.7	W
T _J	Junction Temperature	150	°C
T _{stg}	Storage Temperature	-55~+150	°C
T _L	Lead Temperature for Soldering Purposes(1/8" from case for 10 s)	260	°C
Thermal Resistance Ratings			
R _{thJA}	Maximum Junction-to-Ambient t≤10 s	62.5	°C/W
R _{thJF}	Maximum Junction-to-Foot (Drain) Steady State	41	°C/W


Electrical Characteristics (T_J=25°C Unless Otherwise Specified)


Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
STATIC PARAMETERS						
Drain-source breakdown voltage	V _{(BR)DSS}	V _{GS} =0V, I _D = 250 μA	30			V
Zero gate voltage drain current	I _{DSS}	V _{DS} =30V, V _{GS} = 0V			1	μA
Gate-body leakage current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V			±100	nA
Gate threshold voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D = 250 μA	1.0		2.5	V
Drain-source on-resistance(note1)	R _{Ds(on)}	V _{GS} =10V, I _D = 8A		11.5	14	mΩ
		V _{GS} =4.5V, I _D = 5A		13.8	17	mΩ
Forward transconductance(note1)	g _{FS}	V _{DS} = 15V, I _D = 8A		33		S
Diode forward voltage(note1)	V _{SD}	I _S =3A, V _{GS} = 0V		0.75	1.2	V
DYNAMIC						
Input capacitance	C _{iss}	V _{DS} =15V, V _{GS} =0V, f =1MHz		710		pF
Output capacitance	C _{oss}			146		pF
Reverse transfer capacitance	C _{rss}			63		pF
SWITCHING PARAMETERS (note 2)						
Turn-on delay time	t _{d(on)}	V _{GS} =4.5V, V _{DD} =-15V, R _L =3Ω , R _G =1Ω, I _D =5 A		11	22	ns
Turn-on rise time	t _r			18	35	ns
Turn-off delay time	t _{d(off)}			14	28	ns
Turn-off fall time	t _f			8	16	ns
Total Gate Charge	Q _g	V _{DS} =15V, V _{GS} =4.5V, I _D =8A		54	8	nC
Gate-Source Charge	Q _{gs}			1.6		nC
Gate-Drain Charge	Q _{gd}			1.6		nC

MOSFET TYPICAL CHARACTERISTICS (25°C, unless otherwise noted)


MOSFET TYPICAL CHARACTERISTICS (25°C, unless otherwise noted)

Source-Drain Diode Forward Voltage

On-Resistance vs. Gate-to-Source Voltage

Threshold Voltage

Single Pulse Power, Junction-to-Ambient

Safe Operating Area


MOSFET TYPICAL CHARACTERISTICS (25°C, unless otherwise noted)

 T_C - Case Temperature (°C)

Current Derating*

 T_C - Case Temperature (°C)

Power, Junction-to-Case

 T_A - Ambient Temperature (°C)

Power, Junction-to-Ambient

SOP-8L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.006	0.010
D	4.700	5.100	0.185	0.200
E	3.800	4.000	0.150	0.157
E1	5.800	6.200	0.228	0.244
e	1.270 (BSC)		0.050 (BSC)	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°