P-Channel 20V (D-S) MOSFET

V_{DS}	$R_{DS(on)}$MAX	I_D
-20V	112mΩ@-4.5V	-3.1A
	142mΩ@-2.5V	-2.7A

Features

- Small Package SOT23-3L
- Low Gate Charge
- RoHS Compliant

Applications

- Load Switch

Pin Configuration

SOT23-3L



Packing Information

Device	Marking	Reel Size	Tape Width	Quantity
ECG2301	13D .XXX	7"	8mm	3000pcs

Absolute Maximum Ratings (TJ=25℃ Unless Otherwise Noted)

Symbol	Parameter	Value	Unit
P-MOSFET			
V_{DS}	Drain-Source Voltage	-20	V
V_{GS}	Gate-Source Voltage	±8	V
I_D	Continuous Drain Current	-3.1	A
I_{DM}	Pulse Drain Current	-10	A
P_D	Maximum Power Dissipation	1.6	W
$R_{\theta JA}$	Thermal Resistance from Junction to Ambient	232	℃/W
T_j	Junction Temperature	150	℃
T_{stg}	Storage Temperature	-55~+150	℃
T_L	Lead Temperature for Soldering Purposes(1/8" from case for 10 s)	260	℃
Thermal Resistance Ratings			
R_{thJA}	Maximum Junction-to-Ambient[b]	120	℃/W
	Maximum Junction-to-Ambient[c]	145	℃/W

Electrical Characteristics (T_J =25℃ Unless Otherwise Specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
STATIC PARAMETERS						
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS} =0V, I_D=-250μA	-20			V
Zero gate voltage drain current	I_{DSS}	V_{DS} =-20V,V_{GS} = 0V			-1	μA
Gate-body leakage current	I_{GSS}	V_{GS} =±8V, V_{DS} = 0V			±100	nA
Gate threshold voltage	$V_{GS(th)}$	V_{DS} =V_{GS}, I_D =--250μA	-0.4		-1	V
Drain-source on-resistance(note1)	$R_{DS(on)}$	V_{GS} =-4.5V, I_D =-2.8A		90	112	mΩ
		V_{GS} =-2.5V, I_D =-2.0A		110	142	mΩ
Forward transconductance(note1)	g_{FS}	V_{DS}=-5V,I_D =-2.8A		9.5		S
Diode forward voltage(note1)	V_{SD}	I_S=-0.7A, V_{GS} = 0V		-0.8	-1.2	V
DYNAMIC						
Input capacitance	C_{iss}	V_{DS} =-10V,V_{GS} =0V,f =1MHz		405		pF
Output capacitance	C_{oss}			75		pF
Reverse transfer capacitance	C_{rss}			55		pF
SWITCHING PARAMETERS (note 2)						
Turn-on delay time	$t_{d(on)}$	V_{GS}=-4.5V,V_{DD}=-10V, R_L=10Ω,R_G=1Ω, I_D=-1A		11	20	ns
Turn-on rise time	t_r			35	60	ns
Turn-off delay time	$t_{d(off)}$			30	50	ns
Turn-off fall time	t_f			10	20	ns
Total Gate Charge	Q_g	V_{DS} =-10V,V_{GS} =-4.5V, I_D =-3A		5.5	10	nC
		V_{DS} =-10V,V_{GS} =-2.5V, I_D =-3A		3.3	6	nC
Gate-Source Charge	Q_{gs}			0.7		nC
Gate-Drain Charge	Q_{gd}			1.3		nC

MOSFET TYPICAL CHARACTERISTICS (25°C, unless otherwise noted)



Output Characteristics



Transfer Characteristics



On-Resistance vs. Drain Current and Gate Voltage



Capacitance



Gate Charge



On-Resistance vs. Junction Temperature

TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)



Source-Drain Diode Forward Voltage



On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage



Single Pulse Power



* V_{GS} > minimum V_{GS} at which $R_{DS(on)}$ is specified

SCHOTTKY TYPICAL CHARACTERISTICS (25°C, unless otherwise noted)



Normalized Thermal Transient Impedance, Junction-to-Ambient



Normalized Thermal Transient Impedance, Junction-to-Foot

SOT23-3L Package Information



Top View



Side View

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°